

Eurotaff 530 Transparent Varnish

PUA VARNISH WITH MATTE UV FILTERS

Two-component, water-based aliphatic polyurethane resin varnish for the hardening and anti-dust treatment of concrete pavements and as a finishing layer for coatings on indoor and outdoor surfaces.

Varnish especially indicated as a finishing layer for Coloured Quartz pavements providing a matte finish and improved resistance to yellowing due to UV rays.

INSTRUCTIONS

Mix the components by pouring component B into the container of component A.

Homogenize for 5 minutes using a low-speed stirrer.

Allow the mixture to rest for at least 10 minutes to eliminate the foam created while mixing.

Apply by brush, roller or spray gun as supplied with the product.

TECHNICAL DATA

SOLIDS	43% by weight
POT LIFE	4 hours. NOT VISIBLE
VISCOSITY	2.05 Mix Ford Cup no. 4
SPECIFIC WEIGHT	Comp. a: 1.03 gr/cc Comp. b: 1.16 gr/cc Mixture: 1.05 gr/cc
DRYING TIME	Touch: 4 hours Traffic: 24 hours 80% Total: 48 hours

APPEARANCE	Matte
COLOUR	Colourless

YIELD	100 gr/m ²
APPLICATION TEMP.	Depends on the base.
MIXING RATIO	7.7 A/1B
PACKAGING	2.65 Kg (4 Litres) + 0.35 Kg (1 Litre)

CONSERVATION

** Protect the containers from frost and high temperatures. **