

Eurotaff 530 Transparent Varnish

PUA varnish with matte UV filter

Two-component, water-based aliphatic polyurethane resin varnish for the hardening and anti-dust treatment of concrete pavements and as a finishing layer for coatings on indoor and outdoor surfaces. Varnish especially indicated as a finishing layer for Coloured Quartz pavements providing a matte finish and improved resistance to yellowing due to UV rays.

INSTRUCTIONS

Mix the components by pouring component B into the container of component A.

Homogenize for 5 minutes using a low-speed stirrer.

Allow the mixture to rest for at least 10 minutes to eliminate the foam created while mixing.

Apply by brush, roller or spray gun as supplied with the product.

Specifications

SOLIDS	43% by weight
POT LIFE	4 hours. NOT VISIBLE
VISCOSITY	2.05 Mix Ford Cup no. 4
SPECIFIC WEIGHT	Comp. a: 1.03 gr/cc Comp. b: 1.16 gr/cc Mixture: 1.05 gr/cc
DRYING TIME	Touch: 4 hours Traffic: 24 hours 80% Total: 48 hours
APPEARANCE	Matte
COLOUR	Colourless
YIELD	100 gr/m ²
APPLICATION TEMP.	Depends on the base.
MIXING RATIO	7.7 A/1B
PACKAGING	2.65 Kg (4 Litres) + 0.35 Kg (1 Litre)

CONSERVATION

** Protect Eurotaff 530 from frost and high temperatures. **